

SupaCool R410A



Description

Supa Cool R410A is non-flammable and toxicologically safe.

Supa Cool R410A is preferred internationally as a long-term refrigerant substitute for R22 and it is also an alternative for R13B1.

Applications

- Air conditioners
- Heat pumps
- Cool room storage
- Commercial and industrial refrigeration and as replacement for R13B1 in the low temperature range

Hazard statement(s)

- Contains gas under pressure; may explode if heated.

Prevention statement(s)

- None allocated.

Response statement(s)

- None allocated.

Storage statement(s)

- Protect from sunlight. Store in a well-ventilated place.

Other hazards

- In high concentrations may cause asphyxiation. Contact with liquid may cause cold burns/frostbite.

Signal Word: Warning

UN No.: 3163

Hazard No.: 2TE

Chem Symbol: N/A

Pictograms:





SupaCool R410A

General Specifications

Specifications	12.5 Cyl.	22 Cyl.	65 Cyl.
Cylinder/Pack (101.325kPa @15°C) - kg	8.0	16.0	52.0
Water capacity per cylinder - L	11.0	22.0	65.0
Cylinder Colour	Rose Pink		
Outlet Connection	Type 34		
Package Dimensions (H x W x D) - mm	260 x 404	310 x 505	377 x 859

Cylinder dimensions are approximate – variations may occur due to manufacturing tolerances. Height includes the valve.

Package Sizes Available



Quality Assurance

Supagas Pty Ltd is committed to comply with the requirements of ISO 9001-2015 and to continually improve the effectiveness of our Quality Management System.

Everyone at Supagas understands we must provide a safe environment for both our employees and the wider community. We are therefore committed to implement and maintain a continual improvement approach throughout the organisation whilst also meeting all applicable statutory and regulatory requirements.

NATA Accreditation

The Supagas Laboratory located in Ingleburn, NSW has a NATA

Accreditation (No. 18955). Accredited for compliance with ISO/IEC 17025 and ISO Guide 34, Reference Gas Mixtures prepared to ISO 6142.



Typical Analysis

Chemical Name	Molecular Formula	Composition
Difluoromethane	CH ₂ F ₂	50%
Pentafluoroethane	C ₂ HF ₅	50%

For Further Information

On how we can help you with all your gas and welding needs, drop in to your local Supagas branch or call Customer Service on 13 78 72.